



Cordless Brad Nailer DBN501



18Ga Brad Nailer



Brad Nail Capacity

Length: **15 - 50 mm**

Rapid firing capability

5 shots per second



Offers a similar feel to using a pneumatic nailer and excellent maneuverability

Rapid firing capability

Incorporating a pneumatic spring structure and driven by a BL motor, superior rapid firing capability has been achieved compared to competitors' models.



Tool-less nail jam clearing

Nails can be removed without tools in case of jamming



Bumper

Protects workpieces from scratches or damage.



Belt hook

Convenient for temporarily hanging the tool

LED job light



Main power switch

Indicator

Indicates remaining nail capacity

Slim nose

With an easy-to-aim ejection section for better visibility when driving nails

Window for checking remaining nail quantity

The magazine features a transparent part, enabling the quantity of remaining nails to be checked.



extreme Protection Technology

Anti-dry fire mechanism

Avoids dry firing by locking the contact arm when the remaining nails are 5 to 7.

Driving depth adjustment

For a wide variety of finish applications



Operation mode

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



Accessories / Optional

Brad nail

5,000pcs/box

| Length | Part No. |
|----------------|----------|
| 15mm (5/8") | F-31867 |
| 20mm (3/4") | F-31870 |
| 25mm (1") | F-31883 |
| 30mm (1-3/16") | F-31896 |
| 32mm (1-1/4") | F-31902 |
| 35mm (1-3/8") | F-31915 |
| 38mm (1-1/2") | F-31928 |
| 40mm (1-9/16") | F-31931 |
| 45mm (1-3/4") | F-31944 |
| 50mm (2") | F-31957 |

Charging Time



Fast Charging



| | DC18RC | DC18SD |
|----------------------|--------|---------|
| BL1830B 3.0Ah | 22 min | 60 min |
| BL1840B 4.0Ah | 36 min | 90 min |
| BL1850B 5.0Ah | 45 min | 110 min |
| BL1860B 6.0Ah | 55 min | 130 min |

Cordless Brad Nailer

DBN501

| | | |
|--------------------------|---|--|
| Anti-restart function | Nail capacity | Length: 15 - 50 mm (9/16 - 2") Gauge: 18 Ga |
| Depth Adjustment | Magazine capacity | 110 nails |
| Sequential and Bump-fire | Shot q'ty on a single full battery charge (Battery) | 1,700 pcs |
| Auto Firing Stop | Vibration level (EN60745-2-16) | 2.5 m/s ² or less |
| Built-in Job Light | Vibration K factor (EN60745-2-16) | 1.5 m/s ² |
| Carrying Case | Sound pressure level (EN60745-2-16) | 82 dB(A) |
| | Sound power level (EN60745-2-16) | 93 dB(A) |
| | Noise K factor (EN60745-2-16) | 3 dB(A) |
| | Dimensions (L x W x H) | 246 x 96 x 301 mm (9-11/16 x 3-3/4 x 11-7/8") |
| | Net weight | 3.0 kg (BL1860B) |

Standard Equipment :

DBN501Z : Hook : 346317-0(1)
DBN501RFJ : Hook : 346317-0(1), Connector plastic case (type 4) : 821552-6(1), Inner tray : 836366-0(1), Battery BL1830B : 197605-6(2), Fast Charger : DC18RC (1)



Makita Power Tools India Pvt. Ltd.

Unit II, Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli, Hoskote Taluk, Bengaluru - 560067

Email: info@makita.in

Website: www.makita.in