

■ Also available

**Cordless Portable Band Saw
BP002G**


Max. cutting capacity: 127 mm
Blade length: 1,140 mm
Net weight: 6.6 - 7.8 kg



■ Accessories / Optional

Band saw blade

Width : 13 mm
Thickness : 0.5 mm
Length : 835 mm



Part No.	Type	Width (mm)	No. of teeth per inch	Teeth shape	Application
B-40543	Bi-Metal (5pc.)	3 mm-6 mm	14	 Wave teeth	Plastics and non-ferrous metal. Mild steel, cast steel and cast iron. Hard steel and stainless steel.
B-40559		2 mm- 3 mm	18		
B-40565		less than 2 mm	24		

Stand set

Part No. 1917F0-6



Grip 36 set

Part No. 198043-5



Cutting wax

Part No. 191897-9



■ Charging Time

Battery	Fast Charging	
	DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F/H 8.0Ah	76 min	170 min

*1 Recommended battery

**Cordless Portable Band Saw
PB003G**

Variable Speed	Capacity	Square: 66 x 66 mm (2-5/8 x 2-5/8"), Round: 66 mm (2-5/8")
Brake	Blade speed	0 - 3.2 m/s
Anti-restart function	Blade size	Length: 835 mm (32-7/8"), Width: 13 mm (1/2") Thickness: 0.5 mm (1/64")
Constant Speed	Vibration level	1.4 m/s ² (ENIEC62841-2-20, Mode: Cutting metal)
Built-in Job Light	Uncertainty (K) for Vibration	1.5 m/s ² (ENIEC62841-2-20, Mode: Cutting metal)
	Sound pressure level	82 dB(A) (ENIEC62841-2-20)
	Sound power level	90 dB(A) (ENIEC62841-2-20)
	Uncertainty (K) for Noise	3 dB(A) (ENIEC62841-2-20)
	Dimensions (L x W x H)	392 x 175 x 244 mm (15-1/2 x 6-7/8 x 9-5/8")
	Battery	BL4025
	Net weight	4.0 - 5.2 kg (8.8 - 11.5 lbs.)
	Battery	BL4020 - BL4080F

Standard Equipment :

PB003GZ : Hex. wrench 4 783202-0(1), Portable bandsaw blade 18TPI : B-40559(1)

**Powerful & Fast Cutting
for a wide range of materials**

Cutting speed
about **30%UP**

Cut Carbon steel pipe of 48.6 mm diameter with thickness of 3.7 mm using blade supplied with machine.
*Compared with our 18V model



**Max. Cutting capacity
Round pipe**

ø 66 mm

**Square pipe
66 x 66 mm**

Cutting speed
about **30%UP**

Cut Carbon steel pipe of 48.6 mm diameter with thickness of 3.7 mm using blade supplied with machine.
*Compared with our 18V model



Max. cutting capacity
Round pipe
ø 66 mm
Square pipe
66 x 66 mm

LED job light
A diffusion lens spreads light evenly, reducing blade shadows and making it easier to align the blade with the cutting line.

Minimizes RPM drop under heavy load.

BL MOTOR

High-power Brushless motor

Constant speed control



Work amount on a single full battery charge	
Carbon steel pipe ø48.6 x t 3.7 mm	Approx. 93 pcs Battery: BL4040F
	Approx. 60 pcs Battery: BL4025
Thin steel pipe ø38.1 x t 1.4 mm	Approx. 276 pcs Battery: BL4025

Ensures stable cutting when used with Stand Set

Cutting capacity (with stand attached)

Round pipe: **ø 55 mm**
Square pipe: **55 x 55 mm**

Stand set (option)

Easy Installation
Mount Arm plate* on PB003G, and you can secure the band saw to Stand easily with two Thumb screws* without tool.
* Supplied with Stand set

Stable clamping vise
The Vise assembly is designed to slant backward so that it can press the workpiece against both the Guide fence and Base of the stand at a time, providing secure and stable clamping.



Variable speed control by dial
Blade speed adjustable to match the material.

Dial	Blade Speed	Application
1 [Low]	1.3 m/s	Stainless steel, alloy steel, and other hard-to-cut materials
2	1.5 m/s	Steel materials (solid round bar, structural steel, thick steel pipe, etc.)
3	2.1 m/s	
4	2.5 m/s	
5	2.9 m/s	Steel materials (thin steel pipe, etc.)
6 [High]	3.2 m/s	

Easy positioning of stopper plate without tool

Fixing lever
Stopper plate

Easy installation / removal of blade
Exposed wheel design allows easy blade replacement.

Externally adjustable blade tracking
Easily adjustable using the supplied hex wrench.

Catch bracket
Designed to hit against workpiece in place of the tool body at the end of cutting process. It can protect the resin housing from scratches and damage.

Tool hook
Hangable on ladders, etc.

Water-resistance compatible with XPT