



Cordless Tower Light ML014G

Satisfy Professional's Needs



Max. luminous flux 15,000 lm



For lighting at worksites
without a power source

Continuous use (approx)	at Min luminous flux	at Max luminous flux
with BL4080F	28 h	2 h
with BL18120	20 h	1.6 h



IP rating:
IP56




Delivers wide-area illumination from a high position

Adjustable light angle

The light angle is easily adjustable to suit your application, providing optimal illumination.


The light head rotates 180°
Vertically




Horizontally



Light base rotates 180°
Vertically



Illumination range
(Single-sided)



Forward Direction
about 8 m

With soft-start illumination



Downward



Single-sided



360°



Excellent portability

Lightweight Body &
Integrated Tripod

Lightweight
9.5 kg (tool only)

Height
(folded)
about 1 m



Manually adjustable height

The setup height of light head can be adjusted
from 1,085 to 2,430mm.



Easy tripod setup by slide handle



Brightness adjustment dial

(Stepless: 1,100 - 15,000lm)



Power button

Desired battery can be discharged first.
(by pressing and holding the power button).

Battery capacity
warning lamp

Accessories / Optional

Shoulder belt
Part No. TD00000002



Battery: 40Vmax/18V LXT



Upto two battery can be installed:

- Only one XGT or 18V LXT
- Two; One XGT and One 18V LXT in parallel connection

Anti-Tipping Design

To prevent accidental tipping, the
tripod can be secured to ground
with hook stakes.
(Use commercially available hook
stakes.)



Charging Time

	Fast Charging DC40RA	DC40RC	Fast Charging DC18RC	DC18SD
40Vmax			Not compatible with charger DCB18WA	
BL4020 2.0Ah	22 min	30 min	BL1815N 1.5Ah	15 min
BL4025 2.5Ah	28 min	38 min	BL1820B 2.0Ah	24 min
BL4040/F 4.0Ah	45 min	67 min	BL1830B 3.0Ah	22 min
BL4050F 5.0Ah	50 min	85 min	BL1840B 4.0Ah	36 min
BL4080F/H 8.0Ah	76 min	170 min	BL1850B 5.0Ah	45 min
			BL1860B 6.0Ah	55 min
			BL1890 9.0Ah	85 min
			BL18120 12.0Ah	120 min

Cordless Tower Light ML014G

Soft Start	Luminous flux at 1 m from the light source: 400 - 5,000 lx	1,100 - 15,000 lm
*1 Other conditions (at Max luminous flux - at Min luminous flux)	Continuous use 1*1 (Battery) 3.6 - 48 h (BL4080F and BL18120) Max setup height 2,430 mm (8 ft) Folded position: 290 x 265 x 1,035 mm (11-3/8 x 10-3/8 x 40-3/4") Extended position: 780 x 680 x 1,085 - 2,430 mm (30-3/4 x 26-3/4 x 42-3/4 - 95-1/2")	
	Net weight (with Battery)	12.8 kg (28.2 lbs.) (BL4080F and BL18120)

Standard Equipment : Shoulder belt: TD00000002(1)



Makita Power Tools India Pvt. Ltd.
Unit II, Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067

Email: info@makita.in

Website: www.makita.in